

# OldWood

## REFRACTIVE GROUND

### Application Instructions

*- Professional use -*

1.- The Refractive Ground is used as a sealer before oil varnishes are applied.

Avoids an absorption excess of varnish into the wood which could negatively interfere in the acoustic quality of the instrument.

2.- Refractive Ground can be applied by hand or by brush.

3.- To assure a thin layer spread by hand. Refractive Ground penetrates the wood quickly. It is also possible to spread the product by brush. Be careful not to apply too thick layers or excessively. Drying problems could be occur because of this.

4.- Let it dry under UV light, artificial or natural (are both ok, although UV chamber is recommended). At least 8-10 hours under UV light is needed.

5.- A second layer is recommendable using the same procedure as first layer. At least 8-10 hours under UV light is needed.

### CAUTION

Wear vinyl or nitril gloves. High humidity or too thick an application may increase drying time. Use in a well-ventilated workspace.

Keep out of the reach of children. Petroleum distillate.

Do not ingest and avoid any contact with skin or eyes. Vapor harmful to skin and respiratory tract. Do not dispose of this product into the environment

Old Wood Colours & Varnishes s.l.

Plaza Castilla, 3 – 28046 Madrid – Spain

[www.oldwood1700.com](http://www.oldwood1700.com)

